

1 Identification

- **This product is considered an article.** This Safety Data Sheet is written based on the encapsulated substance or mixture in this article.
- **Product identifier:** Gas purifying filter
- **Trade name:** CRS Indicating Oxygen Trap
- **Article number:** 202236-B, 202237-B, 202806, 202820, 202872, 202236-SS, 202237-SS
- **SDS number:** 991033
- **Application of the substance / the preparation** Gas purification
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Chromatography Research Supplies, Inc.
2601 Technology Drive
Louisville, KY 40299 USA
msds@chromres.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (502) 491-6300
CHEMTREC (24 Hours) 800-424-9300 (U.S.A.)
When Calling from Outside the U.S.A., Dial Your Access Code for the U.S.A., then 1, then 703-527-3887.

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

H251 Self-heating: may catch fire.



GHS07

H302 Harmful if swallowed.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Harmful

Harmful by inhalation and if swallowed.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- **Information concerning particular hazards for human and environment:**
The product has to be labeled due to the calculation procedure of international guidelines.
- **Classification system:**
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2013

Reviewed on 07/29/2013

Trade name: CRS Indicating Oxygen Trap

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Manganese dioxide

Activated Copper oxide

· Hazard statements

Self-heating: may catch fire.

Harmful if swallowed or if inhaled.

Causes serious eye irritation.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store bulk masses greater than 0.5 lbs at temperatures not exceeding 100°F.

Store away from other materials.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2

Fire = 4

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 4

Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

1313-13-9	Manganese dioxide	H302; H332	35-55%
14807-96-6	Talc (Mg3H2(SiO3)4)		0-35%
1317-38-0	Activated Copper oxide	H251; H302	6-25%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2013

Reviewed on 07/29/2013

Trade name: CRS Indicating Oxygen Trap

(Contd. of page 2)

1344-28-1	Aluminum oxide		0-10%
1305-78-8	Calcium oxide	☠ H318	0-5%
1304-28-5	Barium oxide, obtained by calcining witherite	☠ H331; ☠ H302	<1%
14808-60-7	Quartz (SiO ₂)		<2%
1314-13-2	Zinc oxide		<1%
· Additional Components			
7631-86-9	Silicon dioxide, chemically prepared		0-45%
1313-59-3	Sodium oxide		0-5%

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Generally the product does not irritate the skin.

- **After eye contact:** Rinse opened eye for several minutes under running water.

- **After swallowing:** Immediately call a doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **Special hazards arising from the substance or mixture** No further relevant information available.

- **Advice for firefighters**

- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2013

Reviewed on 07/29/2013

Trade name: CRS Indicating Oxygen Trap

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 - Do not open. Becomes hot on exposure to air.
 - Thorough dedusting.
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of dust.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

1313-13-9 Manganese dioxide

PEL	Short-term value: C 5 mg/m ³ as Mn
REL	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³ as Mn
TLV	Long-term value: 0.02* 0.1* mg/m ³ as Mn; *respirable **inhalable fraction

14807-96-6 Talc (Mg₃H₂(SiO₃)₄)

PEL	Long-term value: 20 mppcf ppm (containing <1% Quartz)
REL	Long-term value: 2* mg/m ³ *respirable dust
TLV	Long-term value: 2* mg/m ³ *as respirable fraction; E

1344-28-1 Aluminum oxide

PEL	Long-term value: 15*; 15** mg/m ³ *Total dust; ** Respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *Total dust **Respirable fraction
TLV	Long-term value: 1* mg/m ³ as Al; *as respirable fraction

1305-78-8 Calcium oxide

PEL	Long-term value: 5 mg/m ³
REL	Long-term value: 2 mg/m ³
TLV	Long-term value: 2 mg/m ³

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2013

Reviewed on 07/29/2013

Trade name: CRS Indicating Oxygen Trap

(Contd. of page 4)

1304-28-5 Barium oxide, obtained by calcining witherite

PEL Long-term value: 0.5 mg/m³
as Ba

REL Long-term value: 0.5 mg/m³
as Ba

TLV Long-term value: 0.5 mg/m³
as Ba

14808-60-7 Quartz (SiO₂)

PEL see Quartz listing

REL Long-term value: 0.05* mg/m³
*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m³
*as respirable fraction

1314-13-2 Zinc oxide

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction and fume

REL Short-term value: C 15* 10** mg/m³
Long-term value: 5* 5** mg/m³
*dust only **fume

TLV Short-term value: 10* mg/m³
Long-term value: 2* mg/m³
*as respirable fraction

• **Additional information:** The lists that were valid during the creation were used as basis.

• **Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

• **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:** • Safety glasses with side shields

USA

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2013

Reviewed on 07/29/2013

Trade name: CRS Indicating Oxygen Trap

(Contd. of page 5)

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Solid
Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	• Not ignitable, but may heat rapidly in air with risk of igniting combustible materials in contact with it.
· Ignition temperature:	• Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density at 20 °C (68 °F):	0.8 g/cm ³ (6.676 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Insoluble.
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2013

Reviewed on 07/29/2013

Trade name: CRS Indicating Oxygen Trap

(Contd. of page 6)

- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
---	--	--

1314-13-2 Zinc oxide		
----------------------	--	--

Oral	LD50	> 5000 mg/kg (rat)
------	------	--------------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
---	--	--

7631-86-9	Silicon dioxide, chemically prepared	3
-----------	--------------------------------------	---

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2B
------------	---	----

14808-60-7	Quartz (SiO ₂)	1
------------	----------------------------	---

· NTP (National Toxicology Program)		
--	--	--

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2013

Reviewed on 07/29/2013



Trade name: CRS Indicating Oxygen Trap

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - Do not open cartridge. Contents of cartridge should be treated as a RCRA characteristically hazardous waste (D001, Ignitability) unless all metallic fines are shown to be in the "oxidized" state. Dispose of this product in accordance with applicable local, state and federal regulations. Recover metal components by reprocessing whenever possible.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN3190
· UN proper shipping name	
· DOT	Self-heating solid, inorganic, n.o.s. (Activated Copper oxide)
· ADR	3190 Self-heating solid, inorganic, n.o.s. (Activated Copper oxide)
· IMDG, IATA	SELF-HEATING SOLID, INORGANIC, N.O.S. (Activated Copper oxide)
· Transport hazard class(es)	
· DOT	
	
· Class	4.2 Substances liable to spontaneous combustion.
· Label	4.2
· ADR, IMDG, IATA	
	
· Class	4.2 Substances liable to spontaneous combustion
· Label	4.2
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special marking (ADR):	<ul style="list-style-type: none"> • EHS-Mark required (ADR 2.2.9.1.10) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.
· Special marking (IMDG):	<ul style="list-style-type: none"> • EHS-Mark required (IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.
· Special precautions for user	Warning: Substances liable to spontaneous combustion
· Danger code (Kemler):	40

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2013

Reviewed on 07/29/2013

Trade name: CRS Indicating Oxygen Trap

(Contd. of page 8)

· EMS Number:	F-A,S-J
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Remarks:	<ul style="list-style-type: none"> Product contains less than 30 g self-heating substance. See 49 CFR Ch. 1 § 173.4 for small quantity exceptions.
· ADR	<ul style="list-style-type: none"> Label 6.1 required for single packaging and combination packagings containing inner packagings with Dangerous Goods > 5 L for liquids or > 5 kg for solids.
· Remarks:	<ul style="list-style-type: none"> Product contains less than 30 g self-heating substance.
· IMDG	
· Remarks:	<ul style="list-style-type: none"> Product contains less than 30 g self-heating substance.
· IATA	
· Remarks:	<ul style="list-style-type: none"> Product contains less than 30 g self-heating substance. See IATA Section 2.6 for small quantity exceptions.
· UN "Model Regulation":	UN3190, Self-heating solid, inorganic, n.o.s. (Activated Copper oxide), 4.2, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1344-28-1 | Aluminum oxide

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

14808-60-7 | Quartz (SiO₂)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1313-13-9	Manganese dioxide	D
1304-28-5	Barium oxide, obtained by calcining witherite	CBD
1314-13-2	Zinc oxide	II

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/29/2013

Reviewed on 07/29/2013

Trade name: CRS Indicating Oxygen Trap

(Contd. of page 9)

· TLV (Threshold Limit Value established by ACGIH)		
14807-96-6	Talc ($Mg_3H_2(SiO_3)_4$)	A4
1344-28-1	Aluminum oxide	A4
1304-28-5	Barium oxide, obtained by calcining witherite	A4
14808-60-7	Quartz (SiO_2)	A2

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
14808-60-7	Quartz (SiO_2)	

· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Manganese dioxide

Activated Copper oxide

· **Hazard statements**

Self-heating: may catch fire.

Harmful if swallowed or if inhaled.

Causes serious eye irritation.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store bulk masses greater than 0.5 lbs at temperatures not exceeding 100°F.

Store away from other materials.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Product safety department

· **Contact:** Product Safety Department

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 11)

USA

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/29/2013

Reviewed on 07/29/2013

Trade name: CRS Indicating Oxygen Trap

(Contd. of page 10)

*IATA: International Air Transport Association**ACGIH: American Conference of Governmental Industrial Hygienists**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent*

USA